



HANSENTM

THREADED PIPE FITTINGS



80mm Male Hose Tail and Nut & Hose Tail



80mm Male Hose Tail - SMHT80



80mm Nut & Hose Tail - SNT80

CONVERSIONS
3" BSP — 80mm

Adding to the extensive HANSENTM Threaded Pipe Fittings range

FEATURES & BENEFITS

- Manufactured from High Quality Glass Fibre Reinforced Nylon giving a weather, termite, fungi and bacteria resistance, for longer life, cost effective, low maintenance fittings.
- Precision Heavy Duty Tapered Threads give a Strong Reliable Seal.
- Materials strong enough to minimise potential cross threading.
- Fittings provide flexibility and versatility.
- Suitable for other types of flexible pipe & hoses, i.e. thin wall irrigation tubing, suction and rubber hoses.

SPECIFICATIONS

- Maximum Working Pressure for fitting; 10 bar (1000 kPa. 145 PSI) @ 20°C.
- Fire Rating: UL94HB and UV Stabilised.
- Suitable for many types of fluid. Ask your dealer for details or contact Hansen Products for more information.
- SNT80 Washer material; Thermoplastic Rubber.
- Manufactured from a raw material approved for use with potable (drinkable) water.

INSTALLATION TIPS

- All pipe work must be adequately supported.
- It is recommended that either a thread sealing paste or thread sealing tape be used on all BSPT threaded connections.
- We recommend Loctite 533 I.
- HANSENTM Threaded Pipe Fittings can be used in conjunction with metal fittings.

The No Risk Non-Metallic Fitting

www.hansenproducts.com