



MALE TANK FITTING						
Product Code	T1 BSPF	a mm	b mm	c mm	d mm	e mm
STF(B)15	½" (15mm)	38.6	13.9	5.5	55.0	31.0
STF(B)20	¾" (20mm)	45.1	21.5	6.2	55.0	35.0
STF(B)25	1" (25mm)	54.1	27.7	6.5	55.0	38.0
STF(B)32	1¼" (32mm)	64.1	33.6	7.2	55.0	43.0
STF(B)40	1½" (40mm)	72.0	40.6	8.2	55.0	51.0
STF(B)50	2" (50mm)	84.6	52.6	8.2	55.0	55.0



FOR REFERENCE USE ONLY.
 WITH OUR POLICY OF CONTINUING PRODUCT DESIGN AND DEVELOPMENT, SPECIFICATIONS, CODE NUMBERS AND ITEMS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

© COPYRIGHT: HANSEN PRODUCTS (NZ) LIMITED.

The above stated dimensions apply to both the Black and the White Male Tank Fitting

RECOMMENDED HOLE SAW SIZES

- STF 15mm = 22mm or 7/8" Hole Saw
- STF 20mm = 27mm or 1 1/16" Hole Saw
- STF 25mm = 34mm or 1 3/8" Hole Saw
- STF 32mm = 42mm or 1 5/8" Hole Saw
- STF 40mm = 48mm or 1 7/8" Hole Saw
- STF 50mm = 60mm or 2 3/8" Hole Saw

MINIMUM RECOMMENDED HOLE SIZES

- Hole Size for STF 15mm = 22mm
- Hole Size for STF 20mm = 27mm
- Hole Size for STF 25mm = 34mm
- Hole Size for STF 32mm = 42mm
- Hole Size for STF 40mm = 48mm
- Hole Size for STF 50mm = 60mm