

WORKS AT ANY ANGLE OR POSITION

upside down, on its side or straight up and down.



HIGH QUALITY MATERIALS

Manufactured from strong, non-corrosive UV stabilised materials for a long life.

- Body - High Quality Glass Fibre Reinforced Nylon
- Diaphragms - Durable Long Life Nitrile Rubber
- Spring - High Grade Stainless Steel

INTERCHANGABLE PARTS

Diaphragm and spring are interchangeable with the same size Hansen Check Valve



POTABLE WATER APPROVED

Materials approved for use with Potable (drinkable) Water

AS/NZS 4020

MAXIMUM WORKING PRESSURE

16 Bar (232 psi) @ 20°C

SELF CLEANING

The unique design provides self cleaning as part of the valve operation



Valve Open



Valve Closed

FAST RESPONSE

Smooth Operating Valve for High Efficiency

Available in Sizes 25mm, 32mm, 40mm, 50mm, 63mm BSPT (1", 1 1/4", 1 1/2", 2", 2 1/2" BSPT)

FOOT VALVE SOCK


An accessory that helps filter and stop particles entering the Valve. It also discourages the build up of some menacing forms of marine life.



All Hansen Foot Valves are rigorously hand tested.

FAST AND EASY TO INSTALL

A few simple steps and you're up and running with your new Hansen Foot Valve!



*We recommend Loctite 5331.

EASY IN-LINE SERVICING

Easy access Screw Cap provides in-line servicing for all moving parts.



2. Your Hansen Foot Valve comes ready to install. Connect it directly to end of a threaded pipe, or use a Hansen Male Straight or Reducing Straight Coupling to connect to your pipe. Use thread sealant or thread tape on all threaded connections.*

1. Visit our website to help determine which sized Foot Valve to use; <http://www.hansenproducts.com/products/valve/FV-flow.htm>

HANSEN

Foot Valves

High Performance, Cost Effective Foot Valve

www.hansenproducts.com