

Technical Specifications

Hansen Turbo-Sweep Dimensions

Product	Product	T1	a	b
Description	Code	BSPT	mm	mm
Turbo Sweep Washdown Nozzle	HWDNTS	1-1/2"	99	202



Product Description	Product Code	T1 BSPT	a mm	b mm	c mm	d mm
40x40mm Washdown Hose Tail	HWDHT4040	1-1/2"	49.5 AF	100.0	53.0	39.5
40x32mm Washdown Hose Tail	HWDHT4032	1-1/2"	49.5 AF	100.0	53.0	33.0



Hansen Turbo~Sweep Parts & Materials

Cam Plate - Glass Fibre Reinforced Nylon | Turbo Sweep Body - Glass Fibre **Blade** - Glass Fibre Reinforced Polyketone

Front Plate - Acetal

Clip - Glass Fibre Filled Acetal Key - Glass Fibre Filled Acetal

Blade Housing - Glass Fibre Reinforced Nylon Cone - Glass Fibre Reinforced Nylon

Rear Body - Glass Fibre Reinforced Polyketone

Reinforced Nylon

Tip - Thermoplastic Polyester Elastomer

Turbo Sweep Bumper - Thermoplastic Vulcanizate


O-rings - EPDM

Retaining Screws - Stainless Steel

Hansen Turbo~Sweep Working Pressure

Hansen Turbo-Sweep Maximum Working Pressure; 8 Bar 800 kPa. 116 psi @ 20°C

Hansen Turbo~Sweep Flow Chart



Frequently Asked Questions

- Q How many sizes does the Turbo-Sweep come in?
- A The *Turbo-Sweep* is available in a range of versatile connection styles for 25mm to 50mm washdown hose and male or female threaded end connections for custom applications
- What is the pressure rating?
- A The Hansen Turbo-Sweep is pressure rated to 8 Bar 800 kPa. 116 psi @ 20°C
- What temperature can the water be when using the Hansen Turbo-Sweep?
- A Up to 60° Celsius.
- **Q** Are there replacement parts for the Hansen *Turbo-Sweep*?
- A Yes, there is a range of replacement parts available for the Hansen Turbo'Sweep.
- Is the *Turbo-Sweep* adjustable?
- A Yes, it has a wide range of actions from Jet to Sweep and is quickly adjustable between open to fully closed
- Q How much water does the Turbo-Sweep use?
- A This is determined, in part, by your existing washdown system. The best way to move dirt etc is a combination of flow and velocity, which Hansen have taken into account when designing the
- Q What applications can I use a Turbo-Sweep for?
- A Ideal for yard wash, or any other applications that require a combination of flow, pressure and velocity such as washing vehicles.
- Q What hose clamp can I use on the Turbo-Sweep?
- A Hansen have developed a new clamping system which eliminates the traditional stainless steel clamp method. The new Easy Clamp will not cut your hands or wrist, although any hose clamp can be used.
- I'm sick of having to un-twist my hose every day after washing down - how can you solve this?
- A Hansen have developed a thoroughly modern connection, the Ultimate Swivel that allows you to complete your washdown without the washdown hose twisting, as you make your way around the vards.

HANSEN PRODUCTS (NZ) LIMITED

PO Box 809 • Whangarei • New Zealand P: +64 9 430 4140 F: +64 9 430 4141 E: info@hansenproducts.com W: www.hansenproducts.com

Available From:







www.hansenproducts.com

Best Installed Value

With speed and overall performance in mind the Hansen *Turbo* Nozzle range delivers a robust set of user friendly features designed to make washdown less of a chore and more of a working pleasure.

The Hansen *Turbo Sweep* takes nozzles where no other washdown nozzle has ever been. The ultra modern Dual Action Nozzle combines a highly effective Sweep action that acts as a powerful broom to shift effluent across the yard floor in volume, and with a simple twist action converts to a concentrated jet stream to remove those stubborn dried on areas that other nozzles have difficulty shifting. Not restricted to the yard floor, the Hansen *Turbo Sweep* also serves as an excellent nozzle for the likes of industrial, marine and vehicle washing, delivering the ultimate in 2 in 1 cleaning power.

With over 60 years' experience in manufacturing, Hansen Products knows the importance of fluid delivery, flow and pressure within a pipe system. This has seen Hansen Products build a reputation for providing high performance, easy to use, innovative, simple products that provide our customers with "Best Installed Value".

All Hansen products carry our Limited Lifetime Warranty*

*For more information on our warranty, please visit www.hansenproducts.com/legal.htm

Product Details



HWDNTSPACK Turbo Sweep Nozzle Pack Pack includes: Turbo Twist Washdown Nozzle with 40mm inlet and hose tail adaptors for connecting to 32mm & 40mm washdown hose.



HWDNTS Turbo Sweep Nozzle

Turbo Twist Washdown Nozzle with 40mm inlet.



HWDC Easy Clamp

Replaces dangerous metal clamps with a safe hose clamp that prevents nasty cuts. **Available Sizes:** 40mm, 32mm



HWDSHT Ultimate Swivel - Hose Tail

Helps prevent hose twists at nozzle, in-line or at the hose connection point.

Available Sizes: 50mm x 40mm, 50mm x 32mm



HWDSM Ultimate Swivel - Male BSPT

Threaded swivel for custom applications requiring a swiveled connection.

Available Sizes: 50mm x 40mm, 50mm x 32mm



HWDHT Washdown Hose Tail

40mm BSP thread with 32mm or 40mm hose tail end. **Available Sizes:** 40mm, 32mm

TURBO SWEEP SERVICE KITS:

HWDNTSSK - Sweep Service Kit **HWDNSS** - Ultimate Swivel Service Kit

HMFSCREW - 20mm Maxflo SS Screws

Going Where No Other Nozzle Has Ever Been



connections.

a Hansen Easy Clamp.

when working with wet hands