



Class 1

Building Product Information Sheet

Product name:

Hansen Fast Fit Tapping Saddles

Product description and its intended use (*measurements, materials, usage*):

Compliance: Manufactured in compliance with AS/NZS 4020:2018

Product Code: HTSMD

Description: Mechanical fittings in the size range 32mm up to 63mm, manufactured from nylon, intended to provide a watertight off take from pipe manufactured to AS/NZS 4130:2018. Includes one white seal and one stainless steel securing nut and bolt. All sizes have a range of BSP threaded outlet to connect to outlet fittings.

Hansen Fast Fit Tapping Saddles are coloured black and intended for potable cold water pressure applications underground, and potable cold water pressure applications above ground complying with G12.

Suitable for non potable water applications.

Product identifier (*if applicable*):

HTSMD - Hansen Fast Fit Tapping Saddle

Place of manufacture: ☒ Aotearoa New Zealand ☐ Overseas

Legal and trading name of the manufacturer(s):

Hansen Products (N.Z.) Limited

Address for service:

STREET NAME 16 Union East Street

SUBURB Port Whangarei

CITY, COUNTRY Whangarei, New Zealand

POSTCODE 0110

Website:

www.hansenproducts.co.nz

Email address:

orders@hansenproducts.co.nz

Phone no. (*if applicable*):

09 430 4140

NZBN (*if applicable*):

9429039916716

Legal and trading name of the importer (if applicable):

Address for service:

STREET NAME	SUBURB
-------------	--------

CITY, COUNTRY	POSTCODE
---------------	----------

Website:

Email address:

Phone no. (if applicable):

NZBN (if applicable):

Relevant Building Code clauses:

B2 Durability: Performance Clauses B 2.3.1 (a) (i), (ii) and (iii), (b) and (c)

G12 Water Supply AS 1 Table 1,
G12 Water Supply AS1 2.1.2

G14 Industrial Liquid Waste VM 1 Table 3

Statement on how the building product is expected to contribute to compliance:

B2 Durability: Performance Clauses B 2.3.1 (a) (i), (ii) and (iii), (b) and (c)
Correctly designed and installed pressure systems using Hansen Fast Fit Tapping Saddle fittings will satisfy the performance requirements of both Clause B2.3.1 (a) (50 years - services which are difficult to access or replace) and Clause B2.3.1 (b) (15 years - services which are moderately difficult to access or replace).
Clauses (a) and (b) cover the majority of applications with the exception of pipes used above ground which satisfy the requirements of N.Z.B.C. Clause B 2.3 (c). (5 years - services which are easy to access and replace).

G12 Water Supply AS1 2.1.2 Quotes AS/NZS 4020
- Hansen Fast Fit Tapping Saddle fittings comply with AS/NZS 4020:2018

Compliant with AS/NZS 3500.1 Plumbing and Drainage Part 1 Water Services

- options for compliance set out in section 19 of the Act (regulations, acceptable solution, verification method)
- standard or technical document that describes the performance of the building product or the relevant specifications to which the building product was manufactured
- physical properties of the building product
- how the building product is intended to be used.

Limitations on the use of the building product:

- All fire rated applications.
- Without adequate support to the threaded joints both in above ground and below ground applications.
- Any continuous services above 60 Deg C internal or external temperature, or where specific provision for pressure derating has not been made.
- With glycol / ethylene glycol.
- Where the liquid in the pipe becomes solid (frozen).
- With medical gas, or fuel gas.
- With automotive fuel or oil.
- Use of Hansen Fast Fit Tapping Saddles under driveways, paths or foundations is not recommended.
- Where maximum system pressure in all situations including startup, shutdown, pressure surging and water hammer events exceeds PN16 or 1600KPA.

Design requirements that would support the appropriate use of the building product:

Hansen Fast Fit Tapping Saddles comply with the design requirements of AS3500.1:2021. The method of compliance is via conformance to Appendix B "Demonstrating products and materials are fit for purpose" Section B3.

Installation requirements:

Design & Installation: Hansen Fast Fit Tapping Saddle fittings should be installed in accordance with the following Standards:

- General Installation:
AS/NZS 2033, "Installation of Polyethylene pipe systems"
- Buried Structural Design:
AS/NZS 2566 Part 1 and supplement 1. "Buried Flexible Pipelines - Structural Design"
- Detailed Installation and Site Pressure Testing:
AS/NZS 2566 Part 2 "Installation"
- Hansen published installation recommendations available on Hansen website (www.hansenproducts.co.nz)

Maintenance requirements:

None required in normal service

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?:

☐ Yes ☒ No

If yes, description of the warning or ban under section 26:

Version:

10a

Date:

1 | 0 | 1 | 0 | 2 | 3