

Easy to Install



1. Cut the pipe with pipe cutters, knife or saw. Ensure a square cut of pipe ends. Clean burrs from pipe ends. Keep the pipe end clean and as free of scratches and imperfections as



2. Undo the nut to the last hread, do not remove nut m the body.



3. Insert the pipe into the fitting through the Nut, White Grip Ring & Thrust Ring until it meets resistance at the O-Ring. Give the pipe a firm push past the O-Ring all the way until it hits the final stop point.



4. Firmly hand tighten the nut Use a pair of poly grips for a further half turn past hand tight for final tightening on 40mm fittings and greater.

The hydraulic seal is created when the pipe passes the O-ring. Tightening the nut is to achieve pull out resistance of the pipe.

HANSEN PRODUCTS (NZ) LIMITED PO Box 809 • Whangarei • New Zealand **P:** +64 9 430 4140 **F:** +64 9 430 4141 E: info@hansenproducts.com W: www.hansenproducts.com

Available From:

HANSEN Best Installed Value

Fully Compatible

Hansen *Easy Fit* Compression Fittings are fully compatible with all other Hansen fitting ranges.

ough/Tank Valve Ball Valves & Sloflo Rain Relief Valves Easy Fit Compression Filings Threaded Fittings eveller Tank/Reservoir True Fit Tank Fittings Valve Duick Connec Tapping Saddle

Standards & Approvals

SWRAS Hansen *Easy Fit* Metric Compression Fittings are approved by the Water Research Council in the UK which is the highest recognised water testing organisation in the world.

Hansen Easy Fit Compression Fittings meet the requirements for products in contact with drinking water AS/NZS 4020 as per AS/NZS 4020 Australia & New Zealand drinking water standard. The equivalent standard to AS/NZS4020 is BS 6920.



Hansen Easy Fit Compression Fittings Hansen Easy Fit Compression Fittings have achieved the esteemed WaterMark[™] certification for use in plumbing and drainage installations





The Reliable and World Proven Pipe Connection

MADE FROM **HIGH QUALITY** DURABLE MATERIALS

Manufactured using Best Quality Materials to withstand the harshest weather conditions



WATERMARK APPROVED

WaterMark Certificate of Conformity Level | Evaluated to: AS/NZS 4129:2008 Fittings for polyethylene (PE) pipes for pressure applications Certification No: WMKA21978 WaterMark

EASY TO INSTALL

Reliable leak proof seals are the

hallmark or any Hansen fitting

and that's no exceptions when

it comes to the Easy Fit

Compression range.

The simple

steps make

installation

a breeze



WRAS APPROVED

Hansen Easy Fit Metric Compressio Fittings are approved for use with potable (drinkable) water. The Wate Research Council in the UK is the highest recognised water testing organisation in the world.

I. Cut the pipe with pipe cutters, knife or saw. Ensure a square cut of pipe ends. Clean burrs from pipe ends. Keep the pipe end clean and as free of scratches and imperfections as possible.

> **2.** Undo the nut to the last thread. o not remove It from the

3. Insert the pipe into the fitting through the Nut and various internal components until it meets resistance at the O-Ring. Give the pipe a firm push past the O-Ring all the way until it hits the final stop point.

Firmly hand tighten the nut. Use a pair of poly grips for a further half turn past hand tight for final tightening on 40mm fittings and greater

O-Rina







Heavy Gauge



www.hansenproducts.com

ne hydrau seal is create when the pipe passes the O-rin Fightening the nut is to achieve pull out resistance of the pipe.

Compression Joiners

Compression End Connectors

