



### POSITIVE "CLICK" SMOOTH OPEN/CLOSE ACTION

Smooth action open and close helps reduce surge which can cause damage to your system. Positive 'click' gives the assurance the valve is either on or off.



Male/Female Ball Valves available in sizes 25 to 50mm (1" to 2")

### HIGH QUALITY MATERIALS

- Body & End Caps - Glass Fibre Reinforced Nylon
- Handle - Glass Fibre Reinforced Nylon
- Ball - Polypropylene



### REMOVABLE HANDLES

Removable Handles for Security.



### HAND TESTED

All Hansen Full Flow Ball Valves are rigorously hand tested.

### MULTIPLE CONNECTION OPTIONS

Including Female or Male/Female thread and Medium Density Compression Fitting options



### Frost Friendly

### FROST FRIENDLY

Hansen Ball Valves are Frost Friendly and have been tested in frost conditions.

Frost Friendly Results may vary in freezing conditions.



Store Packaging



AS/NZS 4020



Salt Water Friendly

### CORROSION PROOF & POTABLE WATER APPROVED

Manufactured from Non Corrosive, UV Stabilised Materials. Potable Water & Marine Approved and Salt Water Friendly.

Female Ball Valves available in sizes 15 to 50mm (1/2" to 2")



### FULL FLOW BORE

Unrestricted Full Flow Ball Valve gets the job done faster. Less system strain, lower maintenance costs. High Pressure 16 Bar Rated.

# HANSEN™

## Full Flow Ball Valves

# Full Flow Reliable High Performance Ball Valve

[www.hansenproducts.com](http://www.hansenproducts.com)