

## HIGH QUALITY THREADS

for dependable high pressure connections

## EASY GRIP NUTS

Make fast work for tightening fitting onto pipe

## MADE FROM HIGH QUALITY DURABLE MATERIALS

Manufactured using Best Quality Materials to withstand the harshest weather conditions

## WATERMARK APPROVED

WaterMark Certificate of Conformity – Level I Evaluated to:AS/NZS 4129:2008 - Fittings for polyethylene (PE) pipes for pressure applications  
Certification No: WMKA21978



## HIGH PRESSURE RATED

16bar/235psi for sizes 1/2" to 1-1/2" (20mm to 50mm)



## RELIABLE O-RING & POSITIVE GRIP RING

World proven combination for a reliable watertight seal.



## LARGE RANGE

Large range of fittings in sizes 1/2" to 1-1/2" (20mm to 50mm) provides more options & versatility in new and existing installations, saving time and money




## EASY TO INSTALL

Reliable leak proof seals are the hallmark of any Hansen fitting and that's no exceptions when it comes to the Easy Fit Compression range. The simple steps make installation a breeze





1. Cut the pipe with pipe cutters, knife or saw. Ensure a square cut of pipe ends. Clean burrs from pipe ends. Keep the pipe end clean and as free of scratches and imperfections as possible.



2. Undo the nut to the last thread, do not remove nut from the body.

The hydraulic seal is created when the pipe passes the O-ring. Tightening the nut is to achieve pull out resistance of the pipe.



3. Insert the pipe into the fitting through the Nut, Grip Ring & Thrust Ring until it meets resistance at the O-Ring. Give the pipe a firm push past the O-Ring all the way until it hits the final stop point.

4. Firmly hand tighten the nut. Use a pair of poly grips for a further half turn past hand tight for final tightening on 40mm fittings and greater.



*Easy Fit Heavy Gauge Compression Fittings*

# The Reliable and World Proven Pipe Connection

[www.hansenproducts.com](http://www.hansenproducts.com)